

# ULR-IN-YHO

**INDOOR**

**ULTRA HIGH OUTPUT**



**TECHNICAL SPECIFICATIONS:**

- :: LED: SMD2835 chip spaced 1/3" on center, 39 LED per foot, 0.17 watts each chip
- :: Dimmable using a magnetic driver
- :: Cutting increment: Every 2.5 inches
- :: Working voltage: 24V DC (LED driver required)
- :: Power: 6.7 watts per foot
- :: Lumens: 914 lumens per foot, 24 LM per LED
- :: CRI: 80
- :: Max run: 14'
- :: 120° beam angle
- :: 3M double sided tape is preinstalled
- :: Includes 1 female ribbon-to-power supply connector (Prewired) and 1 male plug for connection to next ribbon (Prewired)
- :: Operating temperature: -4°F - 104°F
- :: IP20
- :: 5-year warranty

**Application:**

- :: Ideal for undercabinet, soffit, display cases and toe kick lighting.



**16.4FT ROLLS**

## 24V INDOOR ULTRA HIGH OUTPUT LED RIBBON

CATALOG NO.	COLOR TEMP	WATTS PER FT.	REEL LENGTH	LUMENS PER FT.	LEDs PER FT.	WIDTH	LED TYPE	MAX RUN
ULR-IN-16F-YHO-50K	5000K	6.7	16.4 ft.	900	39	0.4 in.	SMD2835	14 ft.
ULR-IN-16F-YHO-40K	4000K	6.7	16.4 ft.	880	39	0.4 in.	SMD2835	14 ft.
ULR-IN-16F-YHO-30K	3000K	6.7	16.4 ft.	850	39	0.4 in.	SMD2835	14 ft.
ULR-IN-16F-YHO-27K	2700K	6.7	16.4 ft.	850	39	0.4 in.	SMD2835	14 ft.

## TANDEM COUPLINGS & POWER FEED CABLES

CATALOG NO.	DESCRIPTION	LENGTH
ULR-IN-HO-COUP-6I-WR	Coupling to connect 2 extra high output ribbons	6"
ULR-IN-HO-COUP-3F-WR	Coupling to connect 2 extra high output ribbons	3'
ULR-IN-HO-COUP-NO-WR	Coupling to connect 2 extra high output ribbons	No wire
ULR-IN-HO-CONN-6I-WR	Power feed cable, 1side ribbon connector, 1 side female socket to driver	6"
ULR-IN-HO-CONN-3F-WR	Power feed cable, 1side ribbon connector, 1 side female socket to driver	3'
ULR-IN-HO-CONN-3F-PT	Power feed cable, 1side ribbon connector, 1 side open end	3'
ULR-IN-HO-CONN-10F-PT	Power feed cable, 1side ribbon connector, 1 side open end	10'

**G4**